

LAUNDRY EQUIPMENT**TYPE: 40-45 LB. CAPACITY RIGID MOUNT WASHER-EXTRACTOR**

DRYWEIGHT CAPACITY / VOLUME: Shall be a minimum of 40 lbs./cycle, wash wheel shall be a minimum of 6.35 cu/ft.

CABINET / CYLINDER MATERIAL: Shall be AISI Type 304 (Top/Front/Sides), shall be AISI Type 304 (Inner/Outer Cylinder)

DOOR / DRAIN TO FLOOR (inches): Door bottom to floor shall be no less than 24" and drain center to drain at least 11.5".

EXTRACTION G-FORCE: Shall be a minimum of 103 – G Force (79 – G Force 1 Phase)

CYCLE SELECTION: Unit shall provide a minimum of four (4) cycles types with a total combination of sixteen (16) wash cycles including eight (8) designed for basic and delicate loads and eight (8) specialty cycles for treatment of synthetics.

WATER TEMPERATURE CONTROL: Unit shall permit operator to pre-set wash temperatures from 33° – 194°F to adapt to specific linen treatment specifications and/or government sanitary regulations. Water inlet valve shall be thermostatically controlled.

**PROGRESSIVE COOL DOWN/
CREASE GUARD:** Unit shall be capable of a gradual reduction of water temperature from wash to rinse so to reduce fabric shock/wrinkles. Reduction shall be limited to no more than 7°F per minute until 113° F is reached.

CHEMICAL DISPENSER: Unit shall be equipped with a top mounted four (4)-compartment pre-wash and wash detergent/bleach/softener dispenser. For safety purposes, dispenser cover shall be self-closing and manufactured using flexible material for optimum durability and longevity.

AUTOMATIC CHEMICAL INJECTION: Unit shall provide five (5) independent chemical injection connections for automatic dispensing of liquid chemicals with a minimum of four (4) independent activation signals. For safety purposes all connection ports shall be mounted on the rear of the machine and shall allow for hook-up without removal of the machine's top or rear panel.

**PROGRAM ACCELERATOR/
VISUAL CYCLE INDICATOR:** Unit shall allow operator to manually accelerate program to permit bypass of any program step. Accelerator control and visual cycle indicator shall be conveniently located on the microprocessor control and shall allow operator to monitor cycle progress/position.

WATER SEALS: Machine bearings shall be protected by double seals. Main seal shall be composed of EPDM nitrile rubber for maximum moisture protection.

POWER REQUIREMENT: 208-240/60/3 or 208-240/60/1

MACHINE WARRANTY: 3-Years—From the date of installation on all machine parts, including belts/hoses and components with rubber-like composition. 5-Years—Mainframe, inner cylinder, including shaft and coupler, bearings, bearing housing and seals.

APPROVALS: A minimum of CSA or ETL